


T.B.SILENCE



Features


- Performance cooling with a low-noise profile
- Twister Bearing technology for longer lifetime and low noise
- Manual VR for optimal fan speed control
- Batwing Blades design and Carved Halo Frame for extra 20~30% airflow
- Patented Modular Frame with aluminum ring for enhanced stability of structure
- Detachable fan blades for easy cleaning

Twister Bearing




100K Hours Lifetime

Batwing Blades



Extra 20% ~ 30% Airflow

Halo Frame



Carved Halo Frame



Fan Blades Detachable



Manual Speed Control



Specifications

Item	UCTB8A	UCTB12A
Dimension (mm)	82 x 82 x 25	120 x 120 x 25
Bearing Type	Twister Bearing	
Frame	Carved Halo Frame	
Blades	Batwing Blades	
Blade Number	7	9
Speed (RPM)	800 - 2500 (±10%)	800 - 1500 (±10%)
Air Flow (CFM)	18.11 - 39.08	37.57 - 71.25
Air Flow (m ³ /h)	30.77 - 66.40	63.83 - 121.05
Static Pressure (mm-H ₂ O)	0.676 - 3.202	0.722 - 1.676
Minimal Noise (dBA)	10	10
MTBF (hour)	100,000	100,000
Rated Voltage (V)	12	12
Input Power (W)	2.4	3.6
Input Current (A)	0.2	0.3
Accessory	4 x screws	1 x 3 to 4 pin adaptor
		1 x adhesive tape
Safety & EMC	