



CARD READER ECR301

C







Features

- USB Super Charge port for smartphones and tablets. Compliant with the USB Battery Charging (BC) Specification version 1.2.
- USB 3.0 port and card reader ports in USB 3.0 bandwidth.
- 5-in-1 card readers to access mainstream cards: CF I/II/MD, Micro SD, SD/SDHC/SDXC/MMC/RSMMC, MS/MS PRO/ MS PRO DUO, M2 (MS MICRO)
- With 3 USB 2.0 ports and each hub could charge up to 1.5 A to your smartphones and tablets.
- ONE eSATA port for best convenient.
- LED display for power and access.

Specifications

Memory slots	ECR301
MS Slot	MS, MS-DUO, MS Pro, MS Pro-Duo, MS MagicGate, MS Pro MagicGate, MS-Duo MagicGate, MS Pro-Duo MagicGate, etc.
CF Slot	CF I/II, CF Ultra II, CF Extreme III, Micro Drive Magicstor
SD Slot	SD, mini SD, MMC-I, MMC-II, MMC 4.0, MMC Dual Voltage, RS-MMC, RS-MMC Dual Voltage, RS MMC 4.0, SDHC, SDXC
Micro SD Slot	Micro SD/T-Flash (NO Convert Adapter Required)
M2 PORT	M2 (NO Convert Adapter Required)
Function	ECR301
Power	Bus power : 5V; 0.5A / 0.9A Self power : 5V; 2.4A
Storage Temperature	-10 ~ 85 degrees (Celsius)
Working Temperature	0 ~ 40 degrees (Celsius)
Dimension	101 x 119.5 x 25 mm (L x W x H)
Supported OS	Windows 8, 7, Vista, XP; Mac 10.8.3; Linux OS 2.4X or Higher



www.enermax.com

© 2014 ENERMAX Technology Corporation. All rights reserved. Specifications are subject to change without prior notice. Actual product and accessories may differ from illustrations.Omissions and printing errors excepted. Content of delivery might differ in different countries or areas. Some trademarks may be claimed as the property of others. Jun. 2014